


Specifications Sheet



Motorola Canopy PTP 24100 Lite - High power



Canopy Part Number	2400BHDD
Description	PTP 24100 Lite - High power
Signaling Rate	10 Mbps
Typical LOS Range	5 Mi (8 km)
Typical Aggregate Useful Throughput	7.5 Mbps
Frequency range of band	ISM 2400-2483.5 MHz
Non-overlapping Channels	3
Channel Width	20 MHz
Modulation Type	High Index 2-level Frequency Shift Keying (FSK) optimized for interference rejection
Channel Spacing	every 2.5 MHz
Encryption	DES capable
Latency	2.5 msec
Carrier to Interference ratio (C/I)	-3dB @ 10 Mbps, -10dB @ 20 Mbps at -65dBm
Nominal Receiver Sensitivity (dbm typical)	-86 dBm
Antenna Gain (dBi)	8 dB
EIRP (dBm)	Adjustable
Equivalent Isotropic Radiated Power (EIRP)	Adjustable from 10 mW to 2.0 W
DC Power (typical)	0.34 A @ 24 VDC = 8.2 W
Antenna Beam Width	3 dB antenna beam width 60 degrees, Azimuth and Elevation
Mean Time Between Failure (MTBF)	40 yr
Temperature	-40° C to +55° C (-40° F to +131° F)
Wind Survival	190 km/hr (118 miles/hr)
Dimensions	11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D)
Weight	.45 kg (1 lb)
Access Method	Time Division Duplex (TDD)
Interface	10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP
Network Management	HTTP, TELNET, FTP, SNMP Version 2c
FCC ID	ABZ89FC5808
Industry Canada Certification Number	109W-2400

Specifications subject to change without notice.

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their respective owners. © Motorola, Inc. 2008