

Motorola Canopy

2.4GHz AES AP: Power set to low-adjustable to high



Canopy Part Number	2401APWA
Description	2.4GHz AES AP: Power set to low-adjustable to high
Signaling Rate	10 Mbps
Typical Aggregate Useful Throughput	6.2 Mbps
Frequency range of band	ISM 2400-2483.5 MHz
Non-overlapping Channels	3
Channel Width	20 MHz
Modulation Type	High Index 2-level Frequency Shift Keying (FSK) optimized for interference rejection
Channel Spacing	configurable on 2.5 MHz increments
Encryption	AES capable
Latency	15 msec
Carrier to Interference ratio (C/I)	-3dB @ 10 Mbps
Nominal Receiver Sensitivity (dbm typical)	-86 dBm
Antenna Gain (dBi)	8 dBi
EIRP (dBm)	Adjustable
Equivalent Isotropic Radiated Power (EIRP)	Adjustable from 100mW to 2W
DC Power (typical)	0.3 A @ 24 VDC= 7.2 W
Antenna Beam Width	3 dB antenna beam width 60 degrees, Azimuth and Elevation
Mean Time Between Failure (MTBF)	40 yr
Temperature	-40° C to +55° C (-40° F to +131° F)
Wind Survival	190 km/hr (118 miles/hr)
Dimensions	11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D)
Weight	.45 kg (1 lb)
Access Method	Time Division Duplexing/Time Division Multiple Access (TDD/TDMA)
Interface	10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP
Network Management	HTTP, TELNET, FTP, SNMP Version 2c
FCC ID	ABZ89FC5808
Industry Canada Certification Number	109W-2400
CE	"CE" marked & compliant to EN300 328. DoCs are available at http://www.canopywireless.com/doc.php