

Specifications Sheet



Motorola Canopy

CSM 52200: 5.2 GHz Advantage SM



Canopy Part Number	5250SM
Description	CSM 52200: 5.2 GHz Advantage SM
Market Availability	North America
Signaling Rate	20 Mbps Maximum
Typical LOS Range	2 Mi Max
Typical Aggregate Useful Throughput	14 Mbps Maximum
Frequency range of band	U-NII 5250-5350 MHz
Non-overlapping Channels	3
Channel Width	20 MHz
Modulation Type	High Index 2-level and 4-level Frequency Shift Keying (FSK) optimized for interference rejection
Channel Spacing	configurable on 5 MHz increments
Encryption	DES capable
Latency	5 - 7 msec
Carrier to Interference ratio (C/I)	-3dB @ 10 Mbps, -10dB @ 20 Mbps at -65dBm
Nominal Receiver Sensitivity (dbm typical)	-86 dBm@ 10 Mbps, -79dBm @ 20 Mbps
Antenna Gain (dBi)	7 dBi
EIRP (dBm)	30 dBm
Equivalent Isotropic Radiated Power (EIRP)	1W
DC Power (typical)	0.3 A @ 24 VDC = 7.2 W
Antenna Beam Width	3 dB antenna beam width 60 degrees, Azimuth and Elevation
Mean Time Between Failure (MTBF)	40 yr
Temperature	-40° C to +55° C (-40° F to +131° F)
Wind Survival	190 km/hr (118 miles/hr)
Dimensions	11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D)
Weight	.45 kg (1 lb)
Access Method	Time Division Duplexing/Time Division Multiple Access (TDD/TDMA)
Interface	10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP
Network Management	HTTP, TELNET, FTP, SNMP Version 2c
FCC ID	ABZ89FC3789
Industry Canada Certification Number	109W-5200
NYCE	0202CE08128

Specifications subject to change without notice.

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their respective owners. © Motorola, Inc. 2009