


Specifications Sheet



Motorola Canopy PTP 58100 Full - AES



Canopy Part Number	5701BH20DD
Description	PTP 58100 Full - AES
Market Availability	North America, Europe, South America, Asia
Signaling Rate	20 Mbps
Typical LOS Range	1 Mi (1.6 km)
Typical Aggregate Useful Throughput	14.0 Mbps
Frequency range of band	ISM 5725-5850 MHz
Non-overlapping Channels	6
Channel Width	20 MHz
Modulation Type	High Index 4-level Frequency Shift Keying (FSK) optimized for interference rejection
Channel Spacing	every 5 MHz
Encryption	FIPS 197 certified AES capable
Latency	2.5 msec
Carrier to Interference ratio (C/I)	-3dB @ 10 Mbps, -10dB @ 20 Mbps at -65dBm
Nominal Receiver Sensitivity (dbm typical)	-79 dB
Antenna Gain (dBi)	7dB
EIRP (dBm)	30 dB
Equivalent Isotropic Radiated Power (EIRP)	1 W
DC Power (typical)	0.34 A @ 24 VDC = 8.2 W
Antenna Beam Width	3 dB antenna beam width 60 degrees, Azimuth and Elevation
Mean Time Between Failure (MTBF)	40 yr
Temperature	-40° C to +55° C (-40° F to +131° F)
Wind Survival	190 km/hr (118 miles/hr)
Dimensions	11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D)
Weight	.45 kg (1 lb)
Access Method	Time Division Duplex (TDD)
Interface	10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP
Network Management	HTTP, TELNET, FTP, SNMP Version 2c
FCC ID	ABZ89FC5804
Industry Canada Certification Number	109W-5700

Specifications subject to change without notice.