

11N Multi-Function Gigabit Client Bridge**ECB9500****2.4GH/ 2Tx3R 11N****300Mbps****Client Bridge/AP/ WDS/Repeater**

ECB9500 is a powerful and multi-functioned 11n product with 7 major multi-functions, is designed to operate in every working environment for enterprises.

ECB9500 is a Wireless Network device that delivers up to 6x faster speeds and 7x extended coverage than 802.11g devices. ECB9500 supports home network with superior throughput, performance and unparalleled wireless range. With user-friendly WPS function, it helps users to connect to wireless device simply with a one-push button.

To protect data during wireless transmissions, ECB9500 encrypts all wireless transmissions through WEP data encryption and supports WPA/WPA2. ECB9500 also supports IEEE 802.1x Supplicant function in CB mode. Its MAC address filter allows users to select stations with access to connect network. In addition, the function of user isolation protects private network between client users. ECB9500 thus is the best product to ensure network safety for enterprises.

**Package Content**

- 1* 11N multi-function Gigabit Client Bridge (ECB9500)
- 1* 12V/1A Power Adapter
- 1* Ethernet Cable
- 3* 5dBi 2.4GHz Dipole Antennas
- 1*QIG
- 1*CD (User's Manual)

* Theoretical wireless signal rate based on IEEE standard of 802.11b, g, n chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

** All specifications are subject to change without notice.

| Features | Benefits |
|---|---|
| High Speed Data Rate Up to 300Mbps | Capable of handling heavy data payloads such as MPEG video streaming |
| Gigabit Ethernet | Support up to 1000Mbps networking speed |
| IEEE 802.11n draft Compliant and backward compatible with 802.11b/g | Fully compatible with IEEE 802.11b/g/n devices |
| Multi-Function, 7 functions | Allowing users to select different mode in various environment |
| Point-to-point, Point-to-multipoint Wireless Connectivity | Allowing to transfer data from buildings to buildings |
| WDS (Wireless Distributed System) | Making wireless AP and Bridge mode simultaneously as a wireless repeater |
| Universal Repeater | The easiest way to your wireless network's coverage |
| Support Multi-SSID function (4 SSID) in AP mode | Allowing clients to access different networks through a single access point and to assign different policies and functions for each SSID by manager |
| WPA2/WPA/ IEEE 802.1x support | Powerful data security |
| 802.1x Supplicant support (CB & CR mode) | More powerful data security in Client Bridge mode |
| MAC address filtering in AP mode | Ensuring secure network connection |
| User isolation support (AP mode) | Protecting the private network between client users. |
| PPPoE function support (CR mode) | Easy to access the internet via ISP service authentication |
| Power-over-Ethernet (IEEE802.3af) | Flexible Access Point locations and saving cost |
| Keep personal setting | Keeping the latest setting when firmware upgrade |
| SNMP Remote Configuration Management | Helping administrators to remotely configure or manage the Access Point easily |
| QoS (WMM) support | Enhancing user performance and density |
| WPS push button | WiFi Protected setup within 3 steps to setup the AP easily |

* Theoretical wireless signal rate based on IEEE standard of 802.11b, g, n chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

** All specifications are subject to change without notice.

12/22/2008

Technical Specifications

Hardware Specifications

| | |
|---------------------------|--|
| MCU | RT2880, 266MHz + RT2820 RF |
| Memory | 32MB SDRAM |
| Flash | 8MB |
| Expansion Slots | N/A |
| Physical Interface | <ul style="list-style-type: none">● LAN: One 10/100/1000Mbps● Reset Button● Power Jack● WPS push button (Wi-Fi Protected Setup) |
| LEDs Status | <ul style="list-style-type: none">● Power/ Status● LAN (10/100/1000Mbps)● WLAN (Wireless Connection) |
| Power Requirements | <ul style="list-style-type: none">● Power Supply: 90 to 240 VDC \pm 10%, 50/60 Hz (depends on different countries)● Active Ethernet (Power over Ethernet, IEEE802.3af)- 48 VDC/0.375A● Device: 12V/1A |
| Regulation Certifications | <ul style="list-style-type: none">● FCC Part 15/UL, CE |

* Theoretical wireless signal rate based on IEEE standard of 802.11b, g, n chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

** All specifications are subject to change without notice.

12/22/2008

➤ **RF Specification**

| | |
|-------------------------------|--|
| Frequency Band | 2.400~2.484 GHz |
| Media Access Protocol | Carrier sense multiple access with collision avoidance (CSMA/CA) |
| Modulation Technology | - OFDM: BPSK, QPSK, 16-QAM, 64-QAM - DBPSK, DQPSK, CCK |
| Operating Channels | 11 for North America, 14 for Japan, 13 for Europe |
| Receive Sensitivity (Typical) | - IEEE802.11n MCS8 @ -91dBm MCS15 @ -74dBm - IEEE802.11g (3RX) 6Mbps@ -92dBm 54Mbps@ -75dBm - IEEE802.11b (1RX) 1Mbps@ -93dBm 11Mbps@ -91dBm |
| Available transmit power | - IEEE802.11n/g 19dBm@6~9 Mbps / MCS9 18dBm@12~18 Mbps / MCS11 17dBm@24~36 Mbps / MCS13 16dBm@48~54 Mbps / MCS15 - IEEE802.11b 18dBm@1, 11Mbps |
| Antenna *3 | Omni-directional external antenna TNC type; Peak Gain = 5 dBi (Reverse) |

Software Features

| Topology | Infrastructure | | | | | | | | | | | | | | |
|----------------|---|--------------|----------------------|--------------|----------------------|--|--------------|--------------|--------------|--------------|---|-----|------|-----|----|
| Operation Mode | Client Bridge / Access Point / WDS AP / WDS Bridge / Client Router / Router / Universal Repeater | | | | | | | | | | | | | | |
| LAN | DHCP Server DHCP Client | | | | | | | | | | | | | | |
| Wireless | Wireless Mode – 11b / 11g / 11n / Disable Transmission Rate ➤ 11 b/g: 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 in Mbps ➤ 11n: <table border="1" data-bbox="550 1742 1311 1895"> <thead> <tr> <th rowspan="2">MCS Index</th> <th colspan="2">Guard Interval 800ns</th> <th colspan="2">Guard Interval 400ns</th> </tr> <tr> <th>20MHz (Mbps)</th> <th>40MHz (Mbps)</th> <th>20MHz (Mbps)</th> <th>40MHz (Mbps)</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>6.5</td> <td>13.5</td> <td>7.2</td> <td>15</td> </tr> </tbody> </table> | MCS Index | Guard Interval 800ns | | Guard Interval 400ns | | 20MHz (Mbps) | 40MHz (Mbps) | 20MHz (Mbps) | 40MHz (Mbps) | 0 | 6.5 | 13.5 | 7.2 | 15 |
| MCS Index | Guard Interval 800ns | | Guard Interval 400ns | | | | | | | | | | | | |
| | 20MHz (Mbps) | 40MHz (Mbps) | 20MHz (Mbps) | 40MHz (Mbps) | | | | | | | | | | | |
| 0 | 6.5 | 13.5 | 7.2 | 15 | | | | | | | | | | | |

* Theoretical wireless signal rate based on IEEE standard of 802.11b, g, n chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

** All specifications are subject to change without notice.

12/22/2008

| | | | | | |
|----------|---|------|-------|-------|-------|
| | 1 | 13 | 27 | 14.4 | 30 |
| | 2 | 19.5 | 40.5 | 21.7 | 45 |
| | 3 | 26 | 54 | 28.9 | 60 |
| | 4 | 39 | 81 | 43.3 | 90 |
| | 5 | 52 | 108 | 57.8 | 120 |
| | 6 | 58.5 | 121.5 | 65 | 135 |
| | 7 | 65 | 135 | 72.2 | 157.5 |
| | 8 | 13 | 27 | 14.4 | 30 |
| | 9 | 26 | 54 | 28.9 | 60 |
| | 10 | 39 | 81 | 43.3 | 90 |
| | 11 | 52 | 108 | 57.8 | 120 |
| | 12 | 78 | 162 | 86.7 | 180 |
| | 13 | 104 | 216 | 115.6 | 240 |
| | 14 | 117 | 243 | 130 | 270 |
| | 15 | 130 | 270 | 144.4 | 300 |
| | Signal Strength | | | | |
| | Bandwidth Selection- 40/20 MHz for 11n | | | | |
| Security | WEP Encryption-64/128 bit WPA Personal (WPA-PSK using TKIP or AES) WPA Enterprise (WPA-EAP using TKIP) 802.1x Authenticator 802.1x Supplicant- MD5/TTLS (CB & CR mode) Hide SSID in beacons Multiple SSID with 802.1q VLAN tagging (up to 4 SSIDs) in AP mode MAC Filter(AP mode) WLAN L2 isolation(AP mode) Wireless STA (Client) connected list (Idle/Connection Time, Pkt statistics) | | | | |
| QoS | WMM | | | | |

Management

| | |
|-----------------------|---|
| Configuration | Web-based configuration HTTP / Telnet |
| Firmware Upgrade | Upgrade firmware via web-browser Keep latest setting when f/w update |
| Administrator Setting | Administrator password change |
| Reset Setting | Reboot (press 1 second) Reset to Factory Default (press 10 second) |
| System monitoring | Status, Statistics and Event Log |
| SNMP | v1, v2c |

* Theoretical wireless signal rate based on IEEE standard of 802.11b, g, n chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

** All specifications are subject to change without notice.

12/22/2008

| | |
|-----------------------|---|
| MIB | MIB I, MIB II (RFC1213) and Private MIB |
| Traffic Measurement | Per interface |
| Bandwidth Measurement | IP range and bandwidth management |
| Backup & Restore | Settings through Web |

Environment & Physical

| | |
|---------------------------|--|
| Temperature Range | Operating: 0°C to 45°C (32°F to 113°F) Storage: -20°C to 70°C (-4°F to 158°F) |
| Humidity (non-condensing) | 5%~95% typical |
| Dimensions | 125mm (L) x 108mm (W) x 31mm (H) |
| Weight | 350g |

V1.0

* Theoretical wireless signal rate based on IEEE standard of 802.11b, g, n chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

** All specifications are subject to change without notice.

12/22/2008