



global solutions :  
local support™

## RooTenna® 2 Panel Antenna 4940 to 5850 MHz Operation

The RooTenna® 2 panel antenna offered by Laird Technologies was developed to allow integration of the customer's radio equipment inside the weatherproof compartment. The expanded radio compartment is big enough to house transceivers, amplifiers, and other electronic equipment. Two sizes are available - the regular RooTenna® and a lower profile RooTenna®.

The antenna design utilizes a wideband element array over a solid 8.5" square backplane for consistent performance over a wide bandwidth. The housing is UV stabilized ABS plastic. The backplate is alodine coated aluminum with stainless steel fasteners. All bracket fasteners are stainless steel for corrosion protection. There are qty 4 8-32 threaded standoffs provided inside the enclosure for customer mounting. Included with the Roo2 are a customer mounting plate and a patented RJ45-ECS ethernet connector system.

### Features and Benefits:

- RooTenna®, the antenna with a pouch!
- Compact, low profile 19 dBi antenna gain
- Wideband operation 4940-5850MHz
- Includes patented RJ45-ECS ethernet connector system and customer mounting plate
- Vertical or horizontal polarization, beamwidth 15 deg
- Available with RPSMA, RPTNC, MC Card, MMCX, RPYMMCX and U.FL antenna connector

### Applications

- Integrated radio/antenna units
- High speed subscriber units
- Amplified antennas
- 802.11a applications

For sales information:

Telephone 801-572-3024

E-Mail [sales@pacwireless.com](mailto:sales@pacwireless.com)

or visit: [www.pacwireless.com](http://www.pacwireless.com)



## Specifications

Parameter	Min	Typ	Max	Units
Frequency Range	4940		5850	MHz
VSWR (4940-4990MHz <2.0)		1.5:1		
Impedance		50		OHM
Input Power			20	W
Operating Temperature	-45		+70	Deg C
Gain		19		dBi
3dB Beam Angle (E-Plane)		15		Deg
3dB Beam Angle (H-Plane)		15		Deg
Front to Back	25			dB
Weight		29 (.8)		Oz (kg)
Dimension R2T58W	10.75" x 10.75" x 3.5" (267 x 267 x 89)			Inches (mm)
Inside Dim R2T58W	9" x 9" x 2.25" (229 x 229 x 57)			Inches (mm)
Dimension R2T58LW	10.75" x 10.75" x 2.6" (267 x 267 x 67)			Inches (mm)
Inside Dim R2T58LW	9" x 9" x 1.5" (229 x 229 x 38)			Inches (mm)

## Wind Loading (Lbs.)

Model	100MPH	125 MPH
R2T58-19	27.8	43.4

## System Ordering:

- R2T58W-19-xx 4940-5850MHz 19dBi Rootenna® regular profile
- R2T58LW-19-xx 4940-5850MHz 19dBi Rootenna® low profile

(Please note: Where "xx" appears, please specify connector. Connector options include RPSMA, RPTNC, MC Card, MMCX, RPMMCX and U.FL)

## Notes:

- All shipments F.O.B. Schaumburg, IL 60173
- All antennas carry a 2 Year Warranty

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies domestic terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request.

*Specifications subject to change without notice.*

## Antenna Patterns

