

PoE 8 Port Switch

Features

- High Power 10/100Mb Passive PoE 8 Port Switch
- Remotely Power Equipment thru CAT5 Cable up to 100m
- Extend Ethernet and POE up to 200m
- Up to 2A per Port
- Automatic MDI/MDI-X Crossover
- Automatic Speed and Duplex Sensing
- 2K Self Learning MAC Address Table
- Compact Size
- High Temperature Operation




Applications

- Wireless Access Points and Client Devices
- IP Phone and Security Camera Systems
- Power multiple devices from 1 data cable

Description

The **TP-SW8-NC** Power Over Ethernet (PoE) 10/100Mb switch offered by Tycon Power Systems is a fully automatic high speed 8 port Ethernet switch with up to 2A of PoE power per port. It is a non compliant model for devices which are not 802.3af compliant. The PoE output voltage = the input voltage so it is universal in its application. The DC input power range can be from 12V to 57V. The units supply power to the remote device on the unused Ethernet pins 4,5(V+) and 7,8(V-). The Ethernet spec supports distances up to 100m (328 feet) between the PoE switch and the remote device.

18V, 24V and 48V 150W power supplies are available. There are 2 power inputs for attachment of primary and backup power sources.



Device Pinouts

RJ-45 Port 8 (Data/PoE Input)			RJ-45 Port 1-7 (Data & PoE Out)	
Pin	Symbol	Description	Symbol	Description
1	RX+, V+, V-	Data Rx(+), PoE in	RX+	Data Receive(+)
2	RX-, V+, V-	Data Rx(-), PoE in	RX-	Data Receive(-)
3	TX+, V-, V+	Data Tx(+), PoE in	TX+	Data Transmit(+)
4	V+, V-	PoE in,	+Vdc	DC power(+)
5	V+, V-	PoE in	+Vdc	DC power(+)
6	TX-, V-, V+	Data Tx(-), PoE in	TX-	Data Transmit(-)
7	V-, V+	PoE in	-Vdc	DC power(-)
8	V-, V+	PoE in	-Vdc	DC power(-)

Specifications

TP-SW5	
Ethernet Standard	IEEE802.3/IEEE802.3u (10 base-T/100base-T)
POE Standard (Port 8)	IEEE802.3af , IEEE802.3at (Type 2, Class 4)
Ports	1 data/PoE input and 7 data/PoE output automatic crossover and polarity
Transmission Speed	100 Mbps(100base-T), 10 Mbps(10base-T) Auto-negotiation
Switch Technology	Store and Forward
Protocol	CSMA/CD
Flow Control	IEEE802.3x(full-duplex), Back Pressure(half-duplex)
Data Transmission Rate	148800pps for 100base-T, 14880pps for 10base-T
Address Table	2K MAC, self-learning
Connections	Shielded RJ45
POE Port	Port 1-7, auto power management Pin assignment: TX(1,2), RX(3,6), V+(4,5), V-(7,8)
Maximum POE Power	Port 1-8, 2A Per Port Secondary Wire Terminal Input Max 10A
POE Protection	Over Temperature, Over Current, Over/Under Voltage
LED's	Link (Green On, Yellow On) Activity (Green Blinking, Yellow Blinking) PoE Input Detect-4 pair (Yellow On) PoE Input Detect-2 pair (Yellow Blinking) Power On (Green On) Power On Alarm (Red On)
DC Power Input	12V to 57V, Dual DC Inputs, Reverse Polarity Protected.
Self Consumption	5 Watts
Operating Temperature	-10 to +70°C (14 to 158°F)
Operating Humidity (RH)	5% - 90% (non condensing)
Storage Temperature	-40 to +80°C (-40 to +176°F)
Dimensions (LxWxH)	159 x 116 x 40mm (6.3 x 4.6 x 1.6")
Weight	0.45kg (1lb)

LED STATUS INDICATORS

LED	STATUS	DESCRIPTION
Power	Green	LED ON if either power input (port 8 or wire terminal) has valid power applied
	Red	LED ON if the following condition happened. *Power input under voltage (Vin<12V) *Wire Terminal Power input over voltage (Vin>58V) *PoE over current (>2A)
	Off	No power in DC input
LED	STATUS	DESCRIPTION
P1-P8 Link/Act	Green	A network device is detected at 100Mbps, but no communication activity is detected.
	Green Blinking	This port is transmitting to, or receiving packet from another device at 100Mbps.
	Yellow	A network device is detected at 10Mbps, but no communication activity is detected.
	Yellow Blinking	This port is transmitting to, or receiving packet from another device at 10Mbps.
	Off	No device is detected.
LED	STATUS	DESCRIPTION
P1-P7 PoE PSE	Yellow	A valid Powered Device(PD) is detected and delivering power on this port.
	Off	No PD is detected on this port.
P8 PoE PD	Yellow	4 pairs power source received
	Yellow Blinking	2 pairs power source received
	Off	No PoE power detected on this port



Notes:

- All shipments F.O.B. Draper, UT 84020
- Tycon Power Systems PoE Switches carry a 1 year warranty

System Ordering:

TP-SW8-NC 8 Port 12V-57V non-compliant PoE Switch (no power supply included)

PSHP-xx 18V, 24V or 48V 150W autoranging power supply for TP-SW8-NC, with US Power Cord*

*Add an "E" suffix for Euro power cord

For further information contact:

Tyconpower.com



693 Draper Heights Way Ste 102
Draper, UT 84020
PH: 801-432-0003
FAX: 801-501-7464